BCD325P2 Motorola 800-900

1. Program and name your system. Edit 'System' options.
2. Create and name your site(s). Set site frequencies and site options for each site.
3. Create and name your channel group and edit group options.
4. Program IDs. (max 500 per group)
5. Edit channel options.

Use 1 worksheet for each ID group (max 20 groups). Print only the # of sheets you need.

Motorola System Name	**Sys Number Tag** (,0-999)	**ID Scan/Search** (scan/search)	**Sys Delay** (-10,-5,-2,0,1,2,5,10,30,off)	**Type I Fltmap-**
System Type TYPE I-(800ST,800SP,800 custom) TYPE II-(800ST,800SP,900,800 custom)	**Priority ID Scan** (on,off)	**Set S-Bit** (yes,ignore)	**Set End Code** (analog,analog+digital,ignore)	**Set ID Format** (decimal,HEX)
	Emergency Alert	(tone) (level)	(light) (pattern)	**Set Audio AGC** (analog,digital)
Site Options	**Site Quick Key** (.,0-99)	**Site Startup Key** (.,0-9)	**Site Mod** (auto,NFM,FM)	**Site Attenuator** (on,off)
Site Location Info/range	**Site Lockout** (unlock,temp,lockout)		**Site Hold Time** (0-255 secs)	**P25 Waiting Time** (0-1000)

Edit Band Plan-800 Custom *only*

Band Plan 1	**Lower Base Freq**	**Upper Base Freq**	**Offset**	**Polarity**	**Spacing**
Band Plan 2	**Lower Base Freq**	**Upper Base Freq**	**Offset**	**Polarity**	**Spacing**
Band Plan 3	**Lower Base Freq**	**Upper Base Freq**	**Offset**	**Polarity**	**Spacing**

Group Name	**Group Location Info/range**	**Motorola Grp#** (1-20)	**Grp Quick Key** (.,0-9)	**Grp L/O** (unlock,temp,lockout)

ID#	ID Name	Audio Type	Num Tag	Pri	Alert	Level	Light	L/O	Vol Offset

BCD325P2 Motorola 800-900 Worksheet

ID#	ID Name	Audio Type	Num Tag	Pri	Alert	Level	Light	L/O	Vol Offset