BCD996XT/P2 Motorola VHF/UHF

1. Program and name your system. Edit 'System' options.
2. Create and name your site(s). Set Site options and site frequencies for each site.
3. Create and name your channel group and edit group options.
4. Program IDs. (max 500 per group)
5. Edit channel options.

Use 1 worksheet for each ID group (max 20 groups). Print only the # of sheets you need.

Motorola System Name	**Sys Number Tag** (,0-999)	**Scan/Search** (scan/search)	**Sys Delay** (-10,-5,-2,0,1,2,5,10,30,off)	**Priority ID Scan** (on,off)
	Set S-Bit (on,off)	**Set End Code** (analog,analog+digital,ignore)	**Set ID Format** (decimal,HEX)	**Set Record** (all,marked,off)
System Type TYPE II-(VHF,UHF)	**Emergency Alert**	(tone) (level)	(light) (pattern)	**Set Audio AGC** (analog,digital)

Site Options	**Site Quick Key** (.,0-99)	**Site Startup Key** (.,0-9)	**Site Mod** (auto,NFM,FM)	**Site Attenuator** (on,off)
Site Location Info/range	**Site Lockout** (unlock,temp,lockout)		**Site Hold Time** (0-255 secs)	**P25 Waiting Time** (0-1000)

Edit Band Plan 1	**VHF/UHF Base Freq-**	**VHF/UHF Offset-**	**VHF/UHF Step-**
Edit Band Plan 2	**VHF/UHF Base Freq-**	**VHF/UHF Offset-**	**VHF/UHF Step-**
Edit Band Plan 3	**VHF/UHF Base Freq-**	**VHF/UHF Offset-**	**VHF/UHF Step-**

Group Name	**Group Location Info/range**	**Motorola Grp#** (1-20)	**Grp Quick Key** (.,0-9)	**Grp L/O** (unlock,temp,lockout)

ID#	ID Name	Audio Type	Num Tag	Pri	Alert	Level	Light	Pattern	Record	L/O	Vol Offset

BCD996XT/P2 Motorola VHF/UHF Worksheet

ID#	ID Name	Audio Type	Num Tag	Pri	Alert	Level	Light	Pattern	Record	L/O	Vol Offset